



BS EN 12201 - 2 PE PIPES for Pressure Applications						
Nominal Size (mm)	Mean Outside Diameter (mm)		SDR 7.4	SDR 11	SDR 17	SDR 26
	Min	Max	PN 25	PN 16	PN 10	PN 6
			Min	Min	Min	Min
16	16	16.3	2.3			
20	20	20.3	3	2		
25	25	25.3	3.5	2.3		
32	32	32.3	4.4	3	2	
40	40	40.4	5.5	3.7	2.4	
50	50	50.4	6.9	4.6	3	2
63	63	63.4	8.6	5.8	3.8	2.5
75	75	75.5	10.3	6.8	4.5	2.9
90	90	90.6	12.3	8.2	5.4	3.5
110	110	110.7	15.1	10	6.6	4.2
125	125	125.8	17.1	11.4	7.4	4.8
140	140	140.9	19.2	12.7	7.7	5.4
160	160	161.0	21.9	14.6	9.5	6.2
180	180	181.1	24.6	16.4	10.7	6.9
200	200	201.2	27.4	18.2	11.9	7.7
225	225	226.4	30.8	20.5	13.4	8.6
250	250	251.5	34.2	22.7	14.8	9.6
280	280	281.7	38.3	25.4	16.6	10.7
315	315	316.9	43.1	28.6	18.7	12.1
355	355	357.2	48.5	32.2	21.1	13.6
400	400	402.4	54.7	36.3	23.7	15.3
450	450	452.7	61.5	40.9	26.7	17.2
500	500	503.0		45.4	29.7	19.1
560	560	563.4		50.8	33.2	21.4
630	630	633.8		57.2	37.4	24.1
710	710	716.4			42.1	27.2
800	800	807.2			47.4	30.6
900	900	908.1			53.3	34.4
1000	1000	1009			59.3	38.2
1200	1200	1210.8				45.9
1400	1400	1412.6				53.5
1600	1600	1614.4				61.2

POLYETHYLENE PIPES